



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Stabiloplast Accelerator 448 0002

Revision date: 08.03.2023

Product code: 4480002

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Stabiloplast Accelerator 448 0002

Further trade names

contained in: 448 0004 Stabiloplast Set

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Polymerizationaccelerator

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name: Renfert GmbH
Street: Untere Giesswiesen 2
Place: D-78247 Hilzingen
Telephone: +49 7731 8208-0
e-mail: info@renfert.com
Contact person: Frau Andris
e-mail: silke.andris@renfert.com
Internet: www.renfert.com

1.4. Emergency telephone number:

IRL: 01 809 2566 (Healthcare Professionals) | GB: 0044 151 951 3317 (Health and Safety Executive (HSE) Chemicals)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Flam. Liq. 2; H225

Eye Irrit. 2; H319

STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

acetone

Signal word:

Danger

Pictograms:**Hazard statements**

H225

Highly flammable liquid and vapour.

H319

Causes serious eye irritation.

H336

May cause drowsiness or dizziness.

Precautionary statements

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261

Do not breathe mist/vapours/spray.

P280

Wear protective gloves and eye/face protection.

P337+P313

If eye irritation persists: Get medical advice/attention.

P403+P233

Store in a well-ventilated place. Keep container tightly closed.

Special labelling of certain mixtures

EUH066

Repeated exposure may cause skin dryness or cracking.

Labelling of packages where the contents do not exceed 125 ml**Signal word:**

Danger

Pictograms:**2.3. Other hazards**



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Stabiloplast Accelerator 448 0002

Revision date: 08.03.2023

Product code: 4480002

Page 2 of 8

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Polymerizationaccelerator

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
67-64-1	acetone			> 80 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
99-97-8	N,N-dimethyl-p-toluidine			< 1 %
	202-805-4	612-056-00-9	01-2119956633-31	
	Acute Tox. 2, Acute Tox. 3, Acute Tox. 3, STOT RE 2, Aquatic Chronic 3; H330 H311 H301 H373 H412			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. Limits, M-factors and ATE			
99-97-8	202-805-4	N,N-dimethyl-p-toluidine	< 1 %	
	inhalation: LC50 = 1,4 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 139 mg/kg			

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated, saturated clothing immediately.

After inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

After contact with skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

After ingestion

Rinse mouth immediately and drink 1 glass of water. Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Vapours may cause drowsiness and dizziness. Processing vapours can irritate the respiratory tracts, skin and eyes.

Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder, Carbon dioxide (CO₂), alcohol resistant foam, Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Do not inhale explosion and combustion gases.

In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Stabiloplast Accelerator 448 0002

Revision date: 08.03.2023

Product code: 4480002

Page 3 of 8

6.1. Personal precautions, protective equipment and emergency procedures

General advice

- Provide adequate ventilation.
- Use personal protection equipment.
- Remove all sources of ignition.

6.2. Environmental precautions

- Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

- Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).
- Collect in closed and suitable containers for disposal.

6.4. Reference to other sections

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

- Use only in well-ventilated areas.
- Avoid contact with eyes and skin.
- Do not eat, drink or smoke when using this product.

Advice on protection against fire and explosion

- Vapours can form explosive mixtures with air. Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

- Avoid breathing vapours.
- Avoid contact with skin, eyes and clothes.
- Wash hands before breaks and after work.
- Keep away from food, drink and animal feedingstuffs.

Further information on handling

- If handled uncovered, arrangements with local exhaust ventilation should be used if possible.
- Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

- Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

- Please refer to our internet website for more information. www.renfert.com

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-64-1	Acetone	Acetone	50 mg/L	Urine	End of shift

8.2. Exposure controls



Appropriate engineering controls

- Safe handling: see section 7

Individual protection measures, such as personal protective equipment

Eye/face protection

- Wear eye/face protection.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Stabiloplast Accelerator 448 0002

Revision date: 08.03.2023

Product code: 4480002

Page 4 of 8

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

Suitable material: Butyl caoutchouc (butyl rubber)

Thickness of the glove material: 0,5 mm

Breakthrough time: \geq 240 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Respiratory protection

Use only in well-ventilated areas.

Usually no personal respirative protection necessary.

Respiratory protection necessary at: insufficient ventilation

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	clear
Odour:	characteristic
Odour threshold:	not determined

Test method

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	54 °C
Flammability:	No data available
Lower explosion limits:	2,5 * vol. %
Upper explosion limits:	13,0 * vol. %
Flash point:	- 18 °C DIN 51755 (cc)
Auto-ignition temperature:	535 * °C Literaturwert
Decomposition temperature:	not determined
pH-Value:	not applicable
Viscosity / kinematic:	not determined
Water solubility:	miscible
Partition coefficient n-octanol/water:	log Pow: - 0,24 *
Vapour pressure:	246 * hPa
(at 20 °C)	
Density (at 20 °C):	0,78 - 0,82 g/cm ³
Relative vapour density:	not determined

9.2. Other information**Information with regard to physical hazard classes**

Explosive properties

not explosive.

Vapours can form explosive mixtures with air.

Other safety characteristics

Solvent content: > 80 %

Further Information

* Data apply to the main component.

SECTION 10: Stability and reactivity**10.1. Reactivity**

Vapours can form explosive mixtures with air.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. May form explosive peroxides.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Stabiloplast Accelerator 448 0002

Revision date: 08.03.2023

Product code: 4480002

Page 5 of 8

10.5. Incompatible materials

Violent reaction with: Oxidising agent, strong

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 14040,4 mg/kg; ATE (dermal) 30303,0 mg/kg; ATE (inhalation vapour) 141,41 mg/l; ATE (inhalation dust/mist) 5,051 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
99-97-8	N,N-dimethyl-p-toluidine				
	oral	LD50 139 mg/kg	Mouse	IUCLID	
	dermal	ATE 300 mg/kg			
	inhalation (4 h) vapour	LC50 1,4 mg/l	Rat	IUCLID	
	inhalation dust/mist	ATE 0,05 mg/l			

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (acetone)

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Further information

The product has not been tested. The statement is derived from the properties of the single components.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
99-97-8	N,N-dimethyl-p-toluidine					
	Acute fish toxicity	LC50 46 mg/l	96 h	Pimephales promelas (fathead minnow)	IUCLID	

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone	-0,24
99-97-8	N,N-dimethyl-p-toluidine	2,81

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Stabiloplast Accelerator 448 0002

Revision date: 08.03.2023

Product code: 4480002

Page 6 of 8

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

The product has not been tested. The statement is derived from the properties of the single components. Do not allow uncontrolled discharge of product into the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Send to a hazardous waste incinerator facility under observation of official regulations.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

List of Wastes Code - residues/unused products

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other organic solvents, washing liquids and mother liquors; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 1090
14.2. UN proper shipping name:	ACETON
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3

**Marine transport (IMDG)**

14.1. UN number or ID number:	UN 1090
14.2. UN proper shipping name:	ACETONE (ACETONE SOLUTIONS)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3



Marine pollutant: no

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 1090
14.2. UN proper shipping name:	Acetone
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3

**14.5. Environmental hazards**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Stabiloplast Accelerator 448 0002

Revision date: 08.03.2023

Product code: 4480002

Page 7 of 8

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Further information: see section 6, 7, 8

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2010/75/EU (VOC): 100 % (780 g/l)

Additional information

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water hazard class (D): 2 - obviously hazardous to water

Additional information

Regulation (EC) No. 2037/2000 concerning materials, which cause damage to the ozone layer: not applicable
 REGULATION (EU) 2019/1021 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on persistent organic pollutants: not applicable
 Regulation (EU) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals: not applicable

SECTION 16: Other information**Changes**

Abs. 2, 9, 11, 15 * Data changed compared with the previous version.

Abbreviations and acronyms

PBT: persistent and bioaccumulative and toxic

vPvB: very persistent, very bioaccumulative

CAS: Chemical Abstracts Service (division of the American Chemical Society)

ATE: Acute Toxicity Estimate

LD50: lethal dose, 50%

LC50: lethal concentration, 50%

ADR: Accord européen relatif au transport international des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement concernant le transport international ferroviaire de marchandises Dangereuses (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

VOC: volatile organic compound(s)

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
 H301 Toxic if swallowed.
 H311 Toxic in contact with skin.
 H319 Causes serious eye irritation.
 H330 Fatal if inhaled.
 H336 May cause drowsiness or dizziness.
 H373 May cause damage to organs through prolonged or repeated exposure.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Stabiloplast Accelerator 448 0002

Revision date: 08.03.2023

Product code: 4480002

Page 8 of 8

H412 Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Restricted to professional users.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)