

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

die:master duo

Revision date: 10.09.2025

Product code: 19560600

Page 1 of 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

die:master duo

Further trade names

contained in:

1956 0800 die:master Set red

1956 0900 die:master Set blue

1956 1000 die:master Set gold/silver

1.2. Relevant identified uses of the substance or mixture and uses advised against**Uses advised against**

No information available.

1.3. Details of the supplier of the safety data sheet

Company name: Renfert GmbH
Street: Untere Giesswiesen 2
Place: D-78247 Hilzingen
Telephone: +49 7731 8208-0
E-mail: info@renfert.com
Contact person: Frau Andris
E-mail: silke.andris@renfert.com
Internet: www.renfert.com

1.4. Emergency telephone number: IRL: 01 809 2566 (Healthcare Professionals) | GB: 0044 151 951 3317 (Health and Safety Executive (HSE) Chemicals)**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Flam. Liq. 2; H225

Eye Irrit. 2; H319

STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

butanone

n-butyl acetate

Signal word: Danger**Pictograms:****Hazard statements**

H225

Highly flammable liquid and vapour.

H319

Causes serious eye irritation.

H336

May cause drowsiness or dizziness.

Precautionary statements

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261

Avoid breathing vapours.

P280

Wear protective gloves and eye protection/face protection.

P337+P313

If eye irritation persists: Get medical advice/attention.

P403+P233

Store in a well-ventilated place. Keep container tightly closed.

Special labelling of certain mixtures

EUH066

Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

die:master duo

Revision date: 10.09.2025

Product code: 19560600

Page 2 of 7

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
78-93-3	butanone			< 75 %
	201-159-0	606-002-00-3	01-2119457290-43	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
123-86-4	n-butyl acetate			10 - 25 %
	204-658-1	607-025-00-1	01-2119485493-29	
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated, saturated clothing immediately.

Get medical advice/attention if you feel unwell.

After inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

After contact with skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Rinse mouth immediately and drink 1 glass of water. Do NOT induce vomiting. When in doubt or if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur: Vapours may cause drowsiness and dizziness. Processing vapours can irritate the respiratory tracts, skin and eyes. Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Extinguishing powder, Carbon dioxide (CO₂), alcohol resistant foam, Water spray jet**Unsuitable extinguishing media**

Full water jet

5.2. Special hazards arising from the substance or mixture

Vapours can form explosive mixtures with air.

Thermal decomposition can lead to the escape of irritating gases and vapours.

5.3. Advice for firefighters

Do not inhale explosion and combustion gases.

In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation.

Use personal protection equipment.

Remove all sources of ignition.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).



Safety Data Sheet

according to Regulation (EC) No 1907/2006

die:master duo

Revision date: 10.09.2025

Product code: 19560600

Page 3 of 7

Collect in closed and suitable containers for disposal.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas.
Avoid contact with skin, eyes and clothes.
Do not eat, drink or smoke when using this product.

Advice on protection against fire and explosion

Vapours can form explosive mixtures with air.
Keep away from sources of ignition - No smoking.
Take precautionary measures against static discharges.

Advice on general occupational hygiene

Avoid breathing vapours.
Avoid contact with skin, eyes and clothes.
Wash hands before breaks and after work.
Keep away from food, drink and animal feedingstuffs.

Further information on handling

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

Please refer to our internet website for more information. www.renfert.com

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
78-93-3	Methyl ethyl ketone (MEK) (Butan-2-one)	200	600		TWA (8 h)	
		300	900		STEL (15 min)	
123-86-4	n-Butyl acetate	50	241		TWA (8 h)	
		150	723		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	Butan-2-one	70 µmol/L	Urine	Post shift

8.2. Exposure controls



Appropriate engineering controls

Safe handling: see section 7

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye protection/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.
Suitable material: NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber)
Thickness of the glove material: 0,5 mm
Breakthrough time: >= 240 min
For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above



Safety Data Sheet

according to Regulation (EC) No 1907/2006

die:master duo

Revision date: 10.09.2025

Product code: 19560600

Page 4 of 7

together with the supplier of these gloves.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Respiratory protection

Use only in well-ventilated areas.

Usually no personal respirative protection necessary.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Odour:	characteristic

Test method

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	79 °C
Flammability:	not applicable
Lower explosion limits:	1,2 vol. %
Upper explosion limits:	11,5 vol. %
Flash point:	- 5 °C DIN 51755 (cc)
Auto-ignition temperature:	370 °C
Decomposition temperature:	not determined
pH-Value:	not applicable
Viscosity / kinematic:	not determined
Water solubility:	Immiscible
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	105 hPa
(at 20 °C)	
Density (at 20 °C):	0,80 - 0,88 g/cm ³

9.2. Other information**Information with regard to physical hazard classes****Explosive properties**

not explosive.

Vapours can form explosive mixtures with air.

Further Information

No further relevant information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

Vapours can form explosive mixtures with air.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

No special measures are necessary.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



Safety Data Sheet

according to Regulation (EC) No 1907/2006

die:master duo

Revision date: 10.09.2025

Product code: 19560600

Page 5 of 7

Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (butanone)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Further information

The product has not been tested. The statement is derived from the properties of the single components.

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow uncontrolled discharge of product into the environment.

The product has not been tested. The statement is derived from the properties of the single components.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Send to a hazardous waste incinerator facility under observation of official regulations.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information



Safety Data Sheet

according to Regulation (EC) No 1907/2006

die:master duo

Revision date: 10.09.2025

Product code: 19560600

Page 6 of 7

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1263
14.2. UN proper shipping name: FARBE
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Marine transport (IMDG)

14.1. UN number or ID number: UN 1263
14.2. UN proper shipping name: PAINT
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Marine pollutant: no

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1263
14.2. UN proper shipping name: PAINT
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Further information: see section 6, 7, 8

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions: 88 - 90 %

Directive 2004/42/EC on VOC in paints and varnishes: approx. 750 g/l

Additional information

REGULATION (EU) 2024/590 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 7 February 2024 on substances that deplete the ozone layer, and repealing Regulation (EC) No 1005/2009: not applicable

REGULATION (EU) 2019/1021 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on persistent organic pollutants: not applicable

Regulation (EU) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals: not applicable

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

die:master duo

Revision date: 10.09.2025

Product code: 19560600

Page 7 of 7

SECTION 16: Other information**Changes**

Abs. 15, 16 * Data changed compared with the previous version.

Abbreviations and acronyms

Flam. Liq: Flammable liquid

Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

PBT: persistent and bioaccumulative and toxic

vPvB: Very persistent and very bioaccumulative

CAS: Chemical Abstracts Service (division of the American Chemical Society)

ATE: Acute Toxicity Estimate

LD50: lethal dose, 50%

LC50: lethal concentration, 50%

ADR: Accord européen relatif au transport international des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement concernant le transport international ferroviaire de marchandises Dangereuses (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

VOC: volatile organic compound(s)

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. Restricted to professional users.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)